LF
LuxFlare
ARCHITECTURAL LED LIGHTING

PRODUCT DATASHEET
REV 01 · 2026 · 31/10

OUTDOOR LIGHTING · BOLLARDS

Bollard Light

pathway

LF-BL-C-F-S-10W-3K-IP65

Product overview to be supplied.



MOUNTING

Floor surface

LUMINAIRE DETAILS

Product Code	LF-BL-C-F-S-10W-3K-IP65	Application Area	Outdoor
Product Type	Bollard Light		

PRODUCT DETAILS

Wattage	10 W	Luminous Flux	720 lm	Driver	Internal
Colour Temp.	3000 / 4000K / 6000K	CRI	> 80	Dimming	On-Off
IP Rating	IP65	Beam Angle	120 deg °	Input Voltage	230V AC
Chip Type	COB/SMD	Life Time	50,000 Hours		

PHYSICAL DETAILS

Housing Material	Aluminum	Size	W 120 × H 900 mm	Storage Temp.	-20°C to +80°C
Diffuser Material	PMMA	Cutout	—		
Diffuser Optics	—	Operating Temp.	-20°C to +55°C		


Additional specifications

Lamp life time	50,000 Hours

DIMENSIONAL DR MM



PHOTOMETRIC · POLAR



FINISHES

Black
Dark Gray

LED

Cree · Epistar · Bridglux

DRIVER

Lifud · Eaglerise · LF

SUMMARY

WATTAGE	CCT	INGRESS	FINISH
10	3000 · 4000K · 6000K	65	BK · DG

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.