



OUTDOOR LIGHTING · BOLLARDS

Bollard Light

pathway



LF-BL-F-S-7W-3K IP65

Product overview to be supplied.

MOUNTING

LUMINAIRE DETAILS

Product Code	LF-BL-F-S-7W-3K IP65	Application Area	Outdoor
Product Type	Bollard Light		

PRODUCT DETAILS

Wattage	7 / 10 W	Luminous Flux	770 / 1100 lm	Driver	Integrated
Colour Temp.	3000 K	CRI	> 70	Dimming	Non-Dimmable (On/Off)
IP Rating	IP65	Beam Angle	120°	Input Voltage	230V AC
Chip Type	COB	Life Time	50,000 Hours		


PHYSICAL DETAILS

Housing Material	Alu Die Cast	Size	W 120 × H 500 mm	Size (2)	H 900
Diffuser Material	Polycarbonate (PC)	Operating Temp.	-20°C to +55°C		
Diffuser Optics	Clear	Storage Temp.	-20°C to +80°C		

DIMENSIONAL DRAWING · MM



PHOTOMETRIC · POLAR



FINISHES

RAL 7026

Custom Colour

LED

Bridgelux

Epistar

DRIVER

Luxflare

SUMMARY

WATTAGE

7 · 10

CCT

3000

INGRESS

65

FINISH

CS

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.