LF
LuxFlare
ARCHITECTURAL LED LIGHTING

PRODUCT DATASHEET
REV 01 · 2026 · 31/10

OUTDOOR LIGHTING · BOLLARDS

Bollard Light

pathway

LF-BL-F-S-5W-3K-IP65

Product overview to be supplied.



MOUNTING

Standalone

LUMINAIRE DETAILS

Product Code	LF-BL-F-S-5W-3K-IP65	Application Area	Outdoor
Product Type	Bollard Light		

PRODUCT DETAILS

Wattage	10W / 5W	Luminous Flux	90lm/w	Driver	Internal
Colour Temp.	3000 / 4000 / 6000 K	CRI	> 80	Dimming	On-Off
IP Rating	IP65	Beam Angle	120Deg °	Input Voltage	230V AC
Chip Type	COB	Life Time	50,000 Hours		

PHYSICAL DETAILS

Housing Material	Alu Die Cast	Diffuser Optics	–	Operating Temp.	-20°C to +55°C
Diffuser Material	PC/Glass	Size	Ø 120 × H 800 mm	Storage Temp.	-20°C to +80°C


Additional specifications

Power factor	≥0.85

DIMENSIONAL DRAWING · MM



PHOTOMETRIC · POLAR



FINISHES

Black
Dark Gray

LED

Cree · Bridgelux · Epistar

DRIVER

Lifud · Eaglerise · Luxflare

SUMMARY

WATTAGE	CCT	INGRESS	FINISH
10W · 5W	3000 · 4000 · 6000	65	BK · DG

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.