



OUTDOOR LIGHTING · WALL LUMINAIRES

Wall Light 20W

low-voltage



LFWLWS-20W-3/4/6K-IP65-WH/BK

A surface-mounted outdoor wall light built around two 10 W COB modules for a combined 2360 lm, in a 60 × 140 mm die-cast body. It runs on a 12-24V DC input at a 24° beam angle, rated IP65, in white or black.

MOUNTING

Wall surface

LUMINAIRE DETAILS

Product Code	LFWLWS-20W-3/4/6K-IP65-WH/BK	Application Area	Outdoor
Product Type	Wall Light		

PRODUCT DETAILS

Wattage	20 W	Luminous Flux	2360 lm	Driver	Internal / External
Colour Temp.	3000 / 4000 / 6000 K	CRI	> 80	Dimming	Non-Dimmable (On/Off)
IP Rating	IP65	Beam Angle	24°	Input Voltage	12V-24VDC
Chip Type	Cob	Life Time	50,000 Hours		


PHYSICAL DETAILS

Housing Material	Alu Die Cast	Size	W 60 × H 140 mm	Storage Temp.	-20°C to +80°C
Diffuser Material	Glass	Operating Temp.	-20°C to +55°C		

DIMENSIONAL DRAWING · MM

IMAGE TO BE SUPPLIED

PHOTOMETRIC · POLAR



LIGHT DISTRIBUTION

24°

FINISHES



White



Black

LED

Cree

Bridgelux

DRIVER

Lifud

Luxflare

NZ

SUMMARY

WATTAGE

20

CCT

3000 · 4000 · 6000

INGRESS

65

FINISH

WH · BK

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.