LF
LuxFlare
ARCHITECTURAL LED LIGHTING

PRODUCT DATASHEET
REV 02 · 2026 · 31/10

OUTDOOR LIGHTING · BOLLARDS

Bollard Light

pathway

LF-BL-R-F-S-10W-3K-IP65

Product overview to be supplied.



MOUNTING

Standalone

LUMINAIRE DETAILS

Product Code	LF-BL-R-F-S-10W-3K-IP65	Application Area	Outdoor
Product Type	Bollard Light		

PRODUCT DETAILS

Wattage	10 W	Luminous Flux	1000 lm	Driver	Internal
Colour Temp.	3000K / 4000K / 6000K	CRI	> 80	Dimming	On-Off
IP Rating	IP65	Beam Angle	120°	Input Voltage	230V AC
Chip Type	SMD · COB	Life Time	50,000 Hours		

PHYSICAL DETAILS

Housing Material	Alu Die Cast	Size	Ø 108 × L 900 × W 120 × H 600900 mm	Storage Temp.	-20°C to +80°C
Diffuser Material	Pc / Glass	Operating Temp.	-20°C to +55°C		

Additional specifications

Power Factor	≥0.85


Additional specifications

Lamp life time	50,000 Hours

DIMENSIONAL DR M



PHOTOMETRIC · POLAR



FINISHES

Black
Dark Gray

LED

Cree · Epistar · Bridglux

DRIVER

Lifud · Eaglerise

SUMMARY

WATTAGE	CCT	INGRESS	FINISH
10	3000K · 4000K · 6000K	65	BK · DG

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.