LF
LuxFlare
ARCHITECTURAL LED LIGHTING

PRODUCT DATASHEET
REV 01 · 2026 · 31/08

OUTDOOR LIGHTING · SPIKE & GARDEN

Spike Light

Spike Mounted, Adjustable

LFSGFS-7W-3K-IP65-BK

Product overview to be supplied.



MOUNTING

Floor surface

LUMINAIRE DETAILS

Product Code	LFSGFS-7W-3K-IP65-BK	Application Area	Outdoor
Product Type	Spike Light		


PRODUCT DETAILS

Wattage	7 W	Luminous Flux	560 lm	Driver	External
Colour Temp.	3000 K	CRI	> 80	Dimming	Non-Dimmable (On/Off)
IP Rating	IP65	Beam Angle	36°	Input Voltage	230V AC
Chip Type	SMD	Life Time	50,000 Hours		

PHYSICAL DETAILS

Housing Material	Alu Die Cast	Diffuser Optics	Clear	Operating Temp.	-20°C to +55°C
Diffuser Material	Glass	Size	Ø 56 × W 95 × H 95 mm	Storage Temp.	-20°C to +80°C

DIMENSIONAL DRAWING · MM



FINISHES

Black

LED

Cree · Lumileds · Bridgelux · VS · Tridonic · Epistar

DRIVER

Luxflare

SUMMARY

WATTAGE	CCT	INGRESS	FINISH
7	3000	65	BK

Technical data in accordance with EN 60598-1, EN 62031, EN IEC 63000 (RoHS), EU LVD 2014/35/EU and EN/IEC 60529 (IP code). We reserve the right to make technical and design changes.